

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.	HMIS HAZARD RATING			
SAFETEC OF AMERICA	HEALTH	2	0 = INSIGNIFICANT	3 = HIGH
	FLAMMABILITY	1	1 = SLIGHT	4 = EXTREME
	REACTIVITY	0	2 = MODERATE	
TRANSPORTATION INFORMATION				
PROPER SHIPPING NAME	Not Regulated		REF.	Not Applicable
HAZARD CLASS / PKG. GRP.	None / None		LABEL	None Required
IDENTIFICATION NUMBER	None			

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)	Page 1 of 2
Safetec Burn Spray™	
MANUFACTURER'S NAME Safetec of America, Inc.	EMERGENCY TELEPHONE NUMBER (24 Hours) (800) 255-3924
ADDRESS (NUMBER, STREET, P.O. BOX) 1055 East Delavan Avenue	TELEPHONE NUMBER FOR INFORMATION (716) 895-1822
(CITY, STATE AND ZIP CODE) Buffalo, NY 14215	DATE PREPARED June 04, 2001 SUPERSEDES March 04, 2001

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	OSHA PEL/STEL		ACGIH TLV/TWA/STEL	
			PPM	MG/M ³	PPM	MG/M ³
Lidocaine HCl	6108-05-0	2	None Established		None Established	

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
EYES: Brief contact may cause mild irritation; prolonged contact may cause moderate irritation associated with redness.	Flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
SKIN: Prolonged or repeated skin contact may cause mild irritation.	Flush with clear running water for a minimum of 15 minutes; if irritation persists, seek medical attention.
INGESTION: Small amounts swallowed incidental to normal handling are not likely to cause injury. Swallowing larger amounts may cause injury.	DO NOT induce vomiting; seek immediate medical attention.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; chronic effects are possible with the ingestion of large amounts to the nervous system. Do not use on abraded skin.

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
No additional information						

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin or eye disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

Safetec Burn Spray™

Page 2 of 2

Date: June 04, 2001

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (TOC) 64.8°C	FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component) LEL: Not Applicable UEL: Not Applicable
-----------------------------	-------------------------------------------------------------------------------------------------------------

EXTINGUISHING MEDIAWater, water spray, dry chemicals, chemical foam, CO₂**SPECIAL FIRE FIGHTING PROCEDURES**

DO NOT enter confine fire space without full bunker gear (Helmet with face shield, bunker coats, gloves and rubber boots. Wear NIOSH/MSHA approved self contained breathing apparatus. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

None known

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES**STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED**

Small spills may be flushed with large amounts of water; larger spills should be collected with approved absorbent for disposal.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container(s) tightly closed when not in use. Store in cool, dry area. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION Ordinarily, none required	VENTILATION LOCAL EXHAUST: None Required MECHANICAL (GENERAL): No
PROTECTIVE GLOVES Ordinarily, none required	EYE PROTECTION Ordinarily, none required
OTHER PROTECTIVE CLOTHING OR EQUIPMENT Ordinarily, none required	WORK / HYGIENIC PRACTICES Practice safe work habits. Use according to label instructions.

SECTION 7 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT Approximately 212°F	SPECIFIC GRAVITY (WATER=1) 0.997
VAPOR PRESSURE (mm Hg) Not Determined	MELTING POINT Not applicable
VAPOR DENSITY (AIR=1) Not Determined	pH Approximately 5.0
SOLUBILITY IN WATER Complete	EVAPORATION RATE (n-BUTYL ACETATE=1) Not Determined
APPEARANCE AND ODOR Clear liquid.	% VOLATILES (BY WEIGHT) Not Determined

SECTION 8 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID Extreme temperatures
INCOMPATIBILITIES (MATERIALS TO AVOID) Strong oxidizing agents	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS Decomposition will not occur if handled / stored properly. Thermal decomposition may produce carbon monoxide, small amounts of nitrogen oxides, halogenated compounds or propionaldehyde may also be formed.	
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID None known

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.