

MATERIAL SAFETY DATA SHEET

KWBC03501  
01 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER		HMIS CODES	
KWBC03501		Health	2
		Flammability	4
		Reactivity	0
PRODUCT NAME	KRYLON* Industrial QUIK-MARK* Water-Based Inverted Marking Chalk, APWA Orange		
MANUFACTURER'S NAME	THE SHERWIN-WILLIAMS COMPANY	EMERGENCY TELEPHONE NO.	(216) 566-2917
	Diversified Brands		
	Cleveland, OH 44115		
DATE OF PREPARATION	30-JUL-05	INFORMATION TELEPHONE NO.	(800) 247-3266

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
18	67-63-0	2-Propanol		
		ACGIH TLV	400 ppm	33 mm
		ACGIH TLV	500 ppm STEL	
		OSHA PEL	400 ppm	
		OSHA PEL	500 ppm STEL	
30	115-10-6	Dimethyl Ether		
		ACGIH TLV	Not Available	760 mm
		OSHA PEL	Not Available	
2	124-68-5	2-Amino-2-Methyl-1-Propanol		
		ACGIH TLV	Not Available	0.8 mm
		OSHA PEL	Not Available	
6	471-34-1	Calcium Carbonate		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	15 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE  
 INHALATION of vapor or spray mist.  
 EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE  
 EYES: Irritation.  
 SKIN: Prolonged or repeated exposure may cause irritation.  
 INHALATION: Irritation of the upper respiratory system.  
 May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE  
 Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.  
 Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## =====

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE  
None generally recognized.

## CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

## =====

-----  
Section 4 -- FIRST AID MEASURES  
-----

EYES: Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.

Keep warm and quiet.

INGESTION: Do not induce vomiting.

Get medical attention immediately.

## =====

-----  
Section 5 -- FIRE FIGHTING MEASURES  
-----

## FLASH POINT

LEL

UEL

Propellant &lt; 0 F

2.0

27.0

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## =====

-----  
Section 6 -- ACCIDENTAL RELEASE MEASURES  
-----

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

## =====

-----  
Section 7 -- HANDLING AND STORAGE  
-----

## STORAGE CATEGORY

Not Available

## =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE  
Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

## =====

## Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

## -----

PRECAUTIONS TO BE TAKEN IN USE  
Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

## PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

## EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

## OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====  
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
 -----

PRODUCT WEIGHT 7.24 lb/gal 867 g/l  
 SPECIFIC GRAVITY 0.87  
 BOILING POINT <0 - 335 F <-18 - 168 C  
 MELTING POINT Not Available  
 VOLATILE VOLUME 93 %  
 EVAPORATION RATE Faster than ether  
 VAPOR DENSITY Heavier than air  
 SOLUBILITY IN WATER N.A.  
 pH 7.0  
 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)  
 Volatile Weight 49.90 % Less Water and Federally Exempt Solvents

 =====  
 Section 10 -- STABILITY AND REACTIVITY  
 -----

STABILITY -- Stable  
 CONDITIONS TO AVOID  
 None known.  
 INCOMPATIBILITY  
 None known.  
 HAZARDOUS DECOMPOSITION PRODUCTS  
 By fire: Carbon Dioxide, Carbon Monoxide  
 HAZARDOUS POLYMERIZATION  
 Will not occur

 =====  
 Section 11 -- TOXICOLOGICAL INFORMATION  
 -----

## CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.  
 Reports have associated repeated and prolonged overexposure to solvents  
 with permanent brain and nervous system damage.

## TOXICOLOGY DATA

CAS No.	Ingredient Name				
67-63-0	2-Propanol	LC50	RAT	4HR	Not Available
		LD50	RAT		5045 mg/kg
115-10-6	Dimethyl Ether	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
124-68-5	2-Amino-2-Methyl-1-Propanol	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
471-34-1	Calcium Carbonate	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available

 =====  
 Section 12 -- ECOLOGICAL INFORMATION  
 -----

## ECOTOXICOLOGICAL INFORMATION

No data available.

Continued on page 5

=====  
Section 13 -- DISPOSAL CONSIDERATIONS  
=====

## WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

  
=====Section 14 -- TRANSPORT INFORMATION  
=====

No data available.

  
=====Section 15 -- REGULATORY INFORMATION  
=====

## SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
---------	-------------------	---------	-----------

  
=====

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

## CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

  
=====Section 16 -- OTHER INFORMATION  
=====

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.