

SECO Product Bulletin

Contact your SECO account manager today!

Versatile
and
Economical

- » These laser detectors work with all infrared and red beam rotating lasers.
- » The THUNDER® 54 is designed for general purpose outdoor elevation control. An adjustable rod clamp is included.
- » The THUNDER 56 is designed for interior elevation and alignment applications. The “electronic target” will increase productivity by extending the visible laser’s usable range up to 250 ft.
- » Both units are 100% waterproof and dustproof to IP 67.

Apache THUNDER Laser Detectors

#4851-03 THUNDER 54

#4851-04 THUNDER 56

THUNDER 54 Outdoors

LCD shows arrows for High/Low and a bar for On-Grade

Loud - 100 db beeper can be heard on any jobsite

Rod Clamp is Included

Rod can be purchased separately

THUNDER 56 Indoors

Magnet is built in on top to attach to ceiling grid

LED lights show red for High/Low and green for On-Grade

	THUNDER 54	THUNDER 56
Working Range:	500 ft / 150 m	250 ft / 75 m
Reception Angle:	±45 degrees	±45 degrees
Marking Notch:	1 in / 25 mm	1 in / 25 mm
Detection Height:	1.5 in / 38 mm	1.5 in / 38 mm
Detection Accuracy:	±1/8 in / ±3.0 mm	±1/16 in / ±2.0 mm
Power Supply:	2 x 1.5V “AA”	2 x 1.5V “AA”
Battery Life:	> 100 hours continuous	> 70 hours continuous
Display	LCD (arrow/bar/arrow)	LED’s (red/green/red)
Display Channels:	3	3
Automatic Shutoff:	30 min	30 min
Warranty:	2 Years	2 Years



Contact your SECO account manager today!

If consistent accuracy, long ranges, bright displays, long battery life, all at a low cost is what you’re looking for - the THUNDER laser detector is just the product for you! The THUNDER is known for its professional capabilities that’s priced to fit a budget. It’s small and simple to use, so increase your productivity by purchasing multiple units. Put grade information in the hands of the people that need it, when they need it.